
Паспорт изделия

IEC 60320 C13 connector (socket), 10A, 250V, angled, dismountable, black



Product Code: [LAN-IEC-320-C13/90](#)

IEC 60320 C13 connector (socket), 10A, 250V, angled, dismountable, black

Description

The C13 connector is intended for installation on electric cables for connection to equipment with a C14 inlet. To reduce the depth of the service gap used when connecting, the connector has a cable entry at an angle of 90°.

The connector has 3 screw terminals: phase, neutral and earth.

The connector has a clamping fixation of the cable jacket. The dismountable housing allows multiple mounting/dismounting of the plug on the cable without performance degradation.

Insulator made of glass fiber reinforced polybutylene terephthalate (PBT) is UL-94V-O rated.

Color is black.

Rated voltage:	125/ 230 V AC
Max. allowable voltage:	250 V AC
Rated frequency:	50 Hz
Max. load current:	10 A
Max. working temperature:	75°C
Max. rated voltage:	Short term 2000V
Insulator resistance:	not less than 1000 MOhm

Model range

LAN-IEC-320-C13/90	IEC 60320 C13 connector (socket), 10A, 250V, angled, dismountable, black
--------------------	--

Product descriptions are listed according to the available information at the time of publication. Product specifications can be changed without advanced notification. More detailed and exact information can be obtained from the official partners and distributors of LANMASTER.