Паспорт изделия

Power cord, C13-C20, 3x0.75, 220V, 10A



Product Code: LAN-PP13/20-x.x-yy

Power cord, C13-C20, 3x0.75, 220V, 10A

Description

The power cord is intended to connect electrical equipment with IEC 60320 C20 inlet to AC mains up to 250V.

The cord is made of stranded PVC insulated 3 x 0.75 wire. Connector A is IEC 60320 C13 molded from flame retardant PVC. The inlet on the opposite side (side B) is IEC 60320 C20 molded from flame retardant PVC.

Cable type	3x0.75 PVC
Jacket material	PVC (polyvinyl chloride)
Jacket color	Black, white
Cord length	0.5 m, 1 m, 2 m, 3 m, 5 m
Wire cross-section	0,75 mm^2
Wire type	Stranded
Maximum current	10 A
Maximum voltage	~250 V
Connector A	IEC 60320 C13
Connector B	IEC 60320 C20

Model range

LAN-PP13/20-1.0-BK	Power cord, C13-C20, 3x0.75, 220V, 10A, 1 meter

LAN-PP13/20-3.0-BK	Power cord, C13-C20, 3x0.75, 220V, 10A, 3 meters
LAN-PP13/20-2.0-BK	Power cord, C13-C20, 3x0.75, 220V, 10A, 2 meters
LAN-PP13/20-0.5-BK	Power cord, C13-C20, 3x0.75, 220V, 10A, 0,5 meters
LAN-PP13/20-5.0-BK	Power cord, C13-C20, 3x0.75, 220V, 10A, 5 meters

Product descriptions are listed according to the available information at the time of publication. Product specifications can be changed without advanced notification. More detailed and exact information can be obtained from the official partners and distributors of LANMASTER.