Паспорт изделия

Power cord with lock, C19-Schuko, 3x1.5, 220V, 16A

Product Code: LAN-PP19L/SH-x.x-yy

Power cord with lock, C19-Schuko, 3x1.5, 220V, 16A



Description

The power cord is intended to connect electrical equipment with IEC 60320 C20 inlet to AC mains up to 250V.

The cord is made of stranded PVC insulated 3 x 1.5 wire. Connector A is IEC 60320 C19 molded from flame retardant PVC. The plug on the opposite side (side B) is DIN49441 connector molded from flame retardant PVC.

A special feature of this power cord is that the C19 connector is equipped with a protection (locking) mechanism against accidental or intentional disconnection from the mains.



The connector is inserted into the inlet in the usual way, the mechanism automatically locks the middle contact of the inlet with a locking clamp. The connector has a standard size, so it is compatible with any standard C20 inlets.

For more information about the solution, see the page Physical protection of interfaces.

Cable type	3x1.5 PVC
Jacket material	PVC (polyvinyl chloride)
Jacket color	Black
Cord length	0.5 m, 1 m, 2 m, 3 m, 5 m
Wire cross-section	1,5 mm^2
Wire type	Stranded
Maximum current	16 A
Maximum voltage	~250 V
Connector A	IEC 60320 C19
Connector B	DIN49441

Model range

LAN-PP19L/SH-0.5-BK	Power cord with lock, C19-Schuko, 3x1.5, 220V, 16A, black, 0.5 meters

LAN-PP19L/SH-1.0-BK	Power cord with lock, C19-Schuko, 3x1.5, 220V, 16A, black, 1.0 meter
LAN-PP19L/SH-2.0-BK	Power cord with lock, C19-Schuko, 3x1.5, 220V, 16A, black, 2.0 meters
LAN-PP19L/SH-3.0-BK	Power cord with lock, C19-Schuko, 3x1.5, 220V, 16A, black, 3.0 meters
LAN-PP19L/SH-5.0-BK	Power cord with lock, C19-Schuko, 3x1.5, 220V, 16A, black, 5.0 meters

Product descriptions are listed according to the available information at the time of publication. Product specifications can be changed without advanced notification. More detailed and exact information can be obtained from the official partners and distributors of LANMASTER.