Product Data Sheet

LANMASTER, Category 5e, RJ45 keystone jack, 90-degree, 45-degree, shielded, unshielded, shutterless, white



Part Number: LAN-OK45U5E/90N-WH

LANMASTER, Category 5e, RJ45 keystone jack, 90-degree, 45-degree, shielded, unshielded, shutterless, white for copper structured cabling systems. LANMASTER product information, specifications and part number details.

Description

The module can be used to complete unshielded telecommunication sockets installed in wall trunks, in a wall box, also for installation in modular patch panels (see the compatibility items).

Category 5e compliant.

The module has a standard Keystone form-factor and can be used not only in LANMASTER socket adapters, but also in socket adapters from other manufacturers.

There is an eight-pin RJ-45 socket on the front side of the module, and there is a block for eight contacts of the IDC 110 type on the back side, located at an angle of 90˚ to the front surface of the module.

The insulation displacement contact method is used (IDC) to terminate incoming cable.

There is a wiring diagram for the cable conductors between the IDC pins in accordance with the T568A and T568B wire map for ease of installation.

The module is equipped with a protective insert that provides additional fixation of cable conductors terminated in IDC block and prevents the conductors from being pulled out when the cable is overstretched.

Part Numbers

LAN-OK45U5E/90N-WH	LANMASTER, Category 5e, RJ45 keystone jack, 90-degree, 45-degree, shielded, unshielded, shutterless, white

Specifications are subject to change without notice. For the most current information, consult LANMASTER or an authorized LANMASTER partner/distributor.