
Product Data Sheet

LANMASTER optical patch cord, LSZH, duplex, ST/PC-ST/PC, OM3, 1.0 m

Part Number: LAN-2ST-2ST/OM3-1.0

LANMASTER optical patch cord, LSZH, ST/PC-ST/PC, MM



Description

ST-ST 50/125 patch cord - a piece of optical cable with one or two fibers (with a 3 mm buffer coating), each of which is terminated with an ST optical connector.

The patch cord is used for connection between various network devices or between a network device and a fiber optic cross or inside a fiber optic cross.

The patch cord is used for connection between various network devices or between a network device and a fiber optic cross or inside a fiber optic cross.

Installed connectors are numbered.

Each patch cord comes individually packaged.

Specifications

Insertion loss	≤ 0.3 dB
Number of fibers (cord type)	1, 2 fibers (simplex, duplex)
Fiber optic type	50/125 (OM2/OM3/OM4)
Buffer coating	Low smoke halogen free compound (LSZH)
Jacket	Low smoke halogen free - LSZH (Low Smoke Zero Halogen)
Connector type	ST, 2ST (duplex)
Buffer coating thickness	3 mm

Patch cords with a length of 1, 2, 3 and 5 meters are constantly in stock. Patch cords of other lengths are also available on request with any fiber type (OM1, OM2, OM3, OM4) as simplex or duplex structure with various polishing options (PC, UPC, APC).

Part Numbers

LAN-2ST-2ST/OM3-1.0	LANMASTER optical patch cord, LSZH, duplex, ST/PC-ST/PC, OM3, 1.0 m
LAN-2ST-2ST/OM3-2.0	LANMASTER optical patch cord, LSZH, duplex, ST/PC-ST/PC, OM3, 2.0 m

LAN-2ST-2ST/OM3-3.0	LANMASTER optical patch cord, LSZH, duplex, ST/PC-ST/PC, OM3, 3.0 m
LAN-2ST-2ST/OM3-5.0	LANMASTER optical patch cord, LSZH, duplex, ST/PC-ST/PC, OM3, 5.0 m

Specifications are subject to change without notice. For the most current information, consult LANMASTER or an authorized LANMASTER partner/distributor.