# Product Data Sheet

## Power cord C13-C20, 3 x 1.5 mm², 220 V, 10 A, black, 2 m



**Part Number:** LAN-PPXL13/20-2.0-BK

Power cord C13-C20, 3 x 1.5 mm², 220 V, 10 A, black

## Description

This power cord connects equipment with an IEC 60320 C20 inlet to an AC supply of up to 250 V.

The cord uses a stranded 3 x 1.5 mm² conductor. Connector A is a molded flame-retardant PVC IEC 60320 C13 plug. Connector B is a molded flame-retardant PVC IEC 60320 C20 connector.

| | |
|---|---|
| Cable type | 3 x 1.5 mm² stranded conductor |
| Jacket material | PVC |
| Jacket color | Black |
| Available lengths | 2 m, 3 m |
| Maximum current | 10 A |
| Maximum voltage | 250 V AC |
| Connector A | IEC 60320 C13 |
| Connector B | IEC 60320 C20 |

## Part Numbers

| | |
|---|---|
| LAN-PPXL13/20-2.0-BK | Power cord C13-C20, 3 x 1.5 mm², 220 V, 10 A, black, 2 m |
| LAN-PPXL13/20-3.0-BK | Power cord C13-C20, 3 x 1.5 mm², 220 V, 10 A, black, 3 m |

Specifications are subject to change without notice. For the most current information, consult LANMASTER or an authorized LANMASTER partner/distributor.