Product Data Sheet

Light-emitting diode (LED) 19" luminaire with magnetic mount, 4W, 3 m power cord



Part Number: TWT-CB-LAMP/LED-M

LED 19" luminaire with magnetic mount, 3.6 W, 3 m power cord

Description

The LED luminaire is designed for installation inside or outside the telecommunication cabinet. It has built-in magnets for mounting on a suitable metal flat surface. When using the supplied “S” hook, the luminaire can be hanged if desired.

The package includes:

- luminaire,
- AC/DC power supply (220V/5V) with rocker switch on 3m power cord,
- hanging hook,

Body materials are PVC and duralumin.

Specifications	Description	Value
LED-luminaire	Rated current (µA)	300
	Power consumption (Watt)	3,6 ±5%
	Luminous flux (Lumen)	180
	Number of LEDs (pcs)	30
	Beam angle (degrees)	120
	MTBF (hours)	30000
	Color temperature (K)	6000 - 6500
	Diffuser color	Milky white
	Body color	Silver gray
	Dimensions (Width x Height x Depth, mm)	300,0 x 23,4 x 24,5
Power supply	Input voltage (Volt, AC)	110-240 ±10%
	AC frequency (Herz)	50 / 60
	Output voltage (Volt, DC)	12
	Rated output current (µA DC)	300
	Power cord length (meters)	3
	Cord connector	Ø 3,5 mm
	Power switch	-
Environment	Operating temperature (°C)	0°C - 55°C
	Operating humidity (%)	10% ~ 90%
	Storage temperature (°C)	-20°C ~ 70°C
	Storage humidity (%)	10% ~ 90%

Part Numbers

TWT-CB-LAMP/LED-M	Light-emitting diode (LED) 19" luminaire with magnetic mount, 4W, 3 m power cord

Specifications are subject to change without notice. For the most current information, consult LANMASTER or an authorized LANMASTER partner/distributor.