Паспорт изделия

Power distribution unit, three-phase, vertical, 32A



Product Code: TWT-PDVI3-6x24-CB-32

Power distribution unit, three-phase, vertical, 32A

Description

Three-phase power distribution unit is used for power delivery in telecommunication cabinets and racks. It solves the problems of insufficient length of equipment power cords, ease of access and maintenance.

The unit is equipped with an integrated power cable with three-phase IEC309 plug and a combined set of C19 and C13 sockets. Safety circuit breakers are provided. The unit with circuit breakers includes volt-ammeters to monitor the power supply parameters on each phase.

The PDU is 1.77 meters high and can be installed vertically in 19" cabinets and racks in available locations.

Specification	Value
Power source parameters	3P / 32A / 380V~ 50 Hz
Output sockets (OUT)	6 x IEC60320 C19 24 x IEC60320 C13
Input plug (IN)	IEC60309
On-Off Switch	Safety circuit breaker
Dimensions (WxHxD)	45x60x1772 mm

Model range

TWT-PDVI3-6x24-CB-32	Power distribution unit, three-phase, vertical, A/V-meter, 32A / 380V, 6xC19 + 24xC13, 2.0 m power cord, IEC309 plug

Product descriptions are listed according to the available information at the time of publication. Product specifications can be changed without advanced notification. More detailed and exact information can be obtained from the official partners and distributors of LANMASTER.