Product Data Sheet

Indoor/outdoor FTTH drop cable with messenger wire, flat, steel wire, LSZH, 2xOS2 Ultra, white



Part Number: TWT-OFC-FUS2-SU-LS-T

Indoor/Outdoor fiber optics FTTH cable with messenger and нг(A)-LS jacket

Description

Application:

Indoor/outdoor FTTH subscriber cable with small dimensions and high flexibility. It is used as a distribution cable for aerial installation on communication poles, utility poles and lighting poles, between buildings, inside buildings, in cable ducts and pipes, and along external building facades.

Design: flat cable with optical fibers, strength members and messenger wire under a common low-smoke halogen-free jacket.

The maximum fiber count is 8 fibers.

Weight, dimensions and operating parameters: check the current product datasheet for cable diameter, weight, tensile load, crush resistance, bend radius and temperature range.

Part Numbers

TWT-OFC-FUS2-SU-LS-T	Indoor/outdoor FTTH drop cable with messenger wire, flat, steel wire, LSZH, 2xOS2 Ultra, white
TWT-OFC-FUS4-SU-LS-T	Indoor/outdoor FTTH drop cable with messenger wire, flat, steel wire, LSZH, 4xOS2 Ultra, white

Specifications are subject to change without notice. For the most current information, consult LANMASTER or an authorized LANMASTER partner/distributor.